

FLEXIPOINT™ MATERIAL SAFETY DATA SHEET

SECTION 1: INTRODUCTION & COMPANY DETAILS

Flexitech Pty Ltd ABN 84 060 559 846

Phone: 07 3879 3877

Fax: 07 3879 4299

67 Boundary Road, Carole Park. Qld. 4300

This edition supersedes all previous editions.

Edition Date: 20th January 2003

Emergency telephone number 07 38793877
during normal business hours EST.

**Not Classified as Hazardous
According to the Criteria of Worksafe Australia**

SECTION 2: IDENTIFICATION

PRODUCT NAME: "Flexi-point"
OTHER NAMES: None
U.N. No. Non allocated
DANGEROUS GOODS CLASS: Non allocated
SUBSIDIARY RISK: Non allocated
HAZCHEM CODE: Non allocated
POISON SCHEDULE: Non scheduled
PRODUCT TYPE: water based emulsion
RISK PHRASES: Non allocated
SAFETY PHRASES: Non allocated

MAJOR RECOMMENDED USE: Adhesive for securing
tile roof ridge caps.

RECOMMENDED METHOD OF APPLICATION: Pointing trowel

PHYSICAL DESCRIPTION/PROPERTIES:

APPEARANCE & ODOUR: Coloured paste with mild
acrylic odour.

FLASH POINT: Not flammable

BOILING POINT: >100°C

FLAMMABILITY LIMITS: UPPER: not applicable
LOWER: not applicable

VAPOUR PRESSURE @ 760MM Hg @ 250C: not known

SOLUBILITY IN WATER: miscible

pH: 10-11

SPECIFIC GRAVITY: approx 1.48

EVAPORATION RATE (BUTYL ACETATE = 1) not known

OTHER DATA: none noted

INGREDIENTS:

CHEMICAL ENTITY	CAS No.	PROPORTION
Water based acrylic emulsion		25%
Pozzolans and inert mineral fillers		63%
Rheology modifiers and water		to 100%

No other Hazardous Materials are present in this product at concentrations above the cut off levels as noted in the list of Designated Hazardous Substances, NOHSC:10005 (1994), or as defined in the Approved Criteria For Classifying Hazardous Substances, NOHSC:1008 (1994).

SECTION 3: HEALTH HAZARD INFORMATION

HEALTH EFFECTS: ACUTE

SWALLOWED: Will cause nausea and diarrhoea.

EYE: Abrasive and irritating to the eye.

SKIN: May cause skin irritation and dryness on repeated or prolonged skin contact.

INHALED: Some persons may find the odour causes headache and nausea.

FIRST AID:

SWALLOWED: Do not induce vomiting. Give copious quantities of water and seek medical advice.

EYE: Flush with water for 15 minutes and consult a Doctor.

INHALED: Remove person to fresh air. If breathing stops apply artificial respiration and other First Aid techniques as required and obtain immediate medical assistance.

FACILITIES: No specific First Aid Facilities are required other than those required by relevant legislation such as, for example, the Occupational Health and Safety (First Aid) Regulation 1089 (NSW).

ADVICE

TO DOCTOR: Avoid aspiration risks if vomiting induced. The polymeric component will form films on drying.

SECTION 4: PRECAUTIONS FOR USE

EXPOSURE:

The acrylic emulsion may contain residual monomers, generally to a maximum of 0.3%. The exposure limits as set by Worksafe Australia are as follows:-

Vinyl Acetate CAS # 108-05-04 TWA 10ppm
STEL 20ppm

Butyl Acetate CAS # 141-32-2 TWA 10ppm
Acrylic acid CAS # 79-10-7 TWA 2ppm

VENTILATION:

Ensure adequate ventilation, sufficient to ensure exposure within published limits as noted above. Forced ventilation is not normally required.

PERSONAL PROTECTION:

RESPIRATORY TYPE: An ORGANIC VAPOUR MASK when (AS1716) using in poorly ventilated locations.

GLOVE TYPE: Neoprene.

EYE PROTECTION: Goggles or safety glasses.

CLOTHING: Sufficient to avoid skin contact.

SECTION 5: HANDLING

DANGEROUS GOODS

CLASS/SUBSIDIARY RISK: none allocated

EXPLOSION HAZARD: non flammable

TOXICOLOGICAL DATA: none noted

ECOLOGICAL DATA: none noted